

Method and Apparatus for synchronizing data streams contain-  
ing audio, video and/or other data

5 The invention relates to a method and to an apparatus for  
synchronizing data streams containing audio, video and/or  
other data, wherein some of the data streams are recorded in  
a multiplex on a storage medium and other data streams are  
located out of the data stream multiplex.

10

Background

Optical storage media facilitate recording or replaying of  
15 audiovisual (AV) signals that include one or more video and  
audio data streams and/or other data like subtitles and ser-  
vice information. Based on the Digital Versatile Disc (DVD)  
standard published by www.dvdforum.org pre-recorded movie  
titles are replicated for a mass market using read-only op-  
20 tical discs. Following introduction and proliferation of the  
red laser based DVD standard, a blue laser based media sys-  
tem of even higher capacity has recently been published un-  
der the brand name 'Blu-ray Disc' denoted BD.

25 For nowadays DVDs the content providers create videos for  
many different target countries. This encompasses many dif-  
ferent languages and sub-titles. Additional to this lan-  
guage specific versions of AV material there exists the ap-  
plication of multi-angle and multi-story for optical discs.  
30 In BD applications this possibilities will be enlarged by  
introducing different video formats as SDTV and HDTV videos.  
For optical recording and pre-recording all the different  
elementary streams listed above (video-angle, audio-track,  
subtitle etc.) have to be packetized into a single multiplex  
35 transport stream. During playback the decoder is reading  
this multiplex and decodes those packets belonging to the  
streams selected.

Invention

The invention is based on the recognition of the following fact. Having an AV multiplex carrying all the available components it is not possible to provide additional material, like another sound track or another web-page for a later time. I.e. when a content provider is using an authoring tool for the generation of a BD movie all elementary streams have to be known before starting the generation. It is not possible to add another elementary stream after the AV multiplex production. On the other hand, if a further data stream shall be added later on, this requires a synchronization with the already existing data streams.

Therefore, a problem to be solved by the invention is to allow synchronizing of data streams recorded in a multiplex on a storage medium with further data streams located out of this data stream multiplex.

This problem is solved by the method disclosed in claim 1 and the corresponding apparatus in claim 8.

In principle, the inventive method allows synchronizing data streams containing video, audio and/or other data, wherein some of the data streams are pre-recorded in a multiplex on a storage medium, wherein a navigation file comprises descriptors pointing to parts of said data streams, wherein said descriptors define the arrangement in time for said data streams by means of data sub stream paths.

Advantageous additional embodiments of the invention are disclosed in the respective dependent claims.

Drawings

Exemplary embodiments of the invention are described with

reference to the accompanying drawing, which shows an example of a play list encompassing different video, audio and subtitle stream paths.

5

#### Exemplary embodiments

Figure 1 shows an example of a play list List\_of\_PlayItems encompassing different video, audio and subtitle stream  
10 paths with PlayItems or SubPlayItems, which have to be decoded for playing back of a stream path. A first stream path of PlayItems comprises an AV multiplex stream. Furthermore, several SubPlayItems describe audio, video and subtitle stream paths as depicted.

15

As shown, multiple stream paths may exist in parallel on the global time axis of the PlayList. A stream path may be defined leaky by leaving parts of the time axis empty.

20 Any stream described by a PlayItem or a SubPlayItem may be an elementary stream or again a multiplex of streams.

The inventive synchronization of elementary streams being located out of the main AV multiplex on a optical disc is  
25 described in the following.

Synchronization is thought of for two different cases. The first case is the synchronization of components concerning their relative relation in time. It is determining to which  
30 time the separate components start and end. The second case is the synchronization of components concerning their switching. It is determining points in time and in the binary stream where the decoding of one component can be substituted by decoding another component. The switching of a  
35 video components for example is useful for multi-angle applications.

The preferable medium for such an application will be beyond DVD capabilities e.g. a blu-ray disc to provide the transfer rate needed for out of multiplex bit-stream reading.

5 The out of multiplex semantic provides the ability to playback blu-ray disc AV streams combining different elementary streams inclusive a combination of streams coming from disc and via internet or another storage medium. E.g. there could be a playback of a movie where the video stream is  
10 read from a blu-ray disc the audio stream is read from a hard disc and the sub-title is read from an internet service.

The description for out of multiplex AV material consists of  
15 different files including navigation files and stream files. The navigation files provide all entry points for navigation within the stream files as there are points in the time axis, angle of view, sub-titles and audio channels etc. In a higher layer of the navigation files there exists a list  
20 of play items explaining all stream parts belonging to a playback of the AV material.

In the following a generic syntax for higher level navigation files is described. In the tables 1 till 4 only those  
25 elements are outlined which are mandatory for this invention, i.e. additional elements not described here as well as different orders may be possible.

As defined within Table 1 a playback element on disc which  
30 might be any part of a movie (e.g. a chapter) is described by means of a List\_of\_PlayItems. It consist of length indicating the complete length of the structure in byte, playItems indicating the number of PlayItem() elements and subPlayItems indicating the number of SubPlayItems() within the  
35 List\_of\_PlayItems structure. While at least one PlayItem is mandatory for a List\_of\_PlayItems the SubPlayItems are optional. The time axis of SubPlayItem(s) is referring to the

time axis of the PlayItem(s).

**Table 1: List\_of\_PlayItems – Syntax**

Syntax	No. of bits	Mnemonic
List_of_PlayItems() {		
length	16	uimsbf
playItems	16	uimsbf
...		
subPlayItems	16	uimsbf
...		
for (n=1; n < playItems; n++) {		
PlayItem() {		
...		
}		
for (n=1; n < subPlayItems; n++) {		
SubPlayItem() {		
...		
}		
...		
}		

5 As defined within Table 2 a PlayItem structure consists of length indicating the complete length of the structure in byte, StreamFile describing a link to the elementary stream file, Start\_time describing the presentation start time of the PlayItem within the StreamFile and End\_time describing  
 10 the presentation end time of the PlayItem within the Stream-File.

Additionally it consists of the element "reserved" to preserve byte alignment, Seamless\_presentation\_flag indicating  
 15 if this PlayItem provides seamless transitions between components. The Seamless\_presentation\_flag has the same meaning as within the SubPlayItem (Table 3) and is explained in more details there.

Table 2: PlayItem – Syntax

Syntax	No. of bits	Mnemonic
PlayItem () {		
length	16	uimsbf
StreamFile	...	...
...		
Start_time	32	uimsbf
End_time	32	uimsbf
...		
reserved	11	bslbf
Seamless_presentation_flag	1	bslbf
...		
}		

As defined within Table 3 a SubPlayItem structure is very similar to the structure of a PlayItem. It consists of  
5 length indicating the complete length of the structure in byte, StreamFile describing a link to the elementary stream file, Start\_time describing the presentation start time of the PlayItem within the StreamFile and End\_time describing the presentation end time of the PlayItem within the Stream-  
10 File.

Additionally it consists of the element "reserved" to preserve byte alignment, Seamless\_presentation\_flag indicating if this PlayItem provides seamless transitions between components, Stream\_path\_end indicating the end of a sub stream  
15 path and SubStream\_type an one 8-bit field indicating the type of sub stream path given for the SubPlayItem.

**Table 3: SubPlayItem – Syntax**

Syntax	No. of bits	Mnemonic
SubPlayItem() {		
length	16	uimsbf
StreamFile	...	...
...		
Start_time...	32	uimsbf
End_time...	32	uimsbf
...		
reserved	6	bslbf
Seamless_presentation_flag	1	bslbf
Stream_path_end	1	bslbf
SubStream_type	8	bslbf
...		
}		

As defined within Table 4 the SubStream\_type defines the type of SubPlayItem. This can be an auxiliary audio stream path for audio dubbing, a video stream path, an audio stream path, a subtitle stream path or a graphics stream path. The value 6 till 255 can be used for future stream path formats.

**Table 4: SubStream\_type**

SubStream_type	Meaning
0	reserved for future use
1	Auxiliary audio stream path
2	Video stream path
3	Audio stream path
4	Subtitle stream path
5	Graphics stream path
6-255	reserved for future use

An alternative definition of the SubStream\_type is possible as shown in Table 5. The advantage of divining an auxiliary transport stream path instead of different elementary stream paths is, that any elementary stream can again be embedded within another multiplex stream, i.e. several different subtitles may be multiplexed together within a single file.

Table 5: SubStream\_type

SubStream_type	Meaning
0	reserved for future use
1	Auxiliary audio stream path
2	Auxiliary transport stream path
3-255	reserved for future use

Seamless\_presentation\_flag supports the case of synchroniza-  
tion concerning seamless switching of components during  
5 playback.

The Seamless\_presentation\_flag is located within the Play-  
Item/SubPlayItem and indicates if the transport stream ref-  
erenced to by PlayItem/SubPlayItem is supporting seamless  
10 transitions between its elementary streams. If Seam-  
less\_presentation\_flag is set "true", all elementary streams  
within the transport stream obey the seamless transition re-  
strictions.

15 The seamless transition restrictions are providing Splice  
Points within the elementary stream. Splice Points are  
points at which the decoding of one elementary stream can be  
stopped and the decoding of another can be started without  
having any noticeable effect during playback, presuming that  
20 both elementary streams have been encoded by obeying the  
seamless transition restrictions. The generation of Splice  
Points is reached during encoding by defining a mandatory  
GOP raster, e.g. a fixed GOP length, and by limiting the re-  
quired buffer size, to avoid buffer overflows when switching  
25 different elementary streams during decoding.

A typical application for seamless transitions are multi-  
angle videos. A multi-angle video provides different camera  
angles for a video e.g. one camera within the race-car, an-  
30 other showing the box, one showing the finish line etc.  
When the multi-angle video is played back the user can  
switch seamless between this different camera tracks.



Stream\_path\_end and SubStream\_type support the case of synchronization concerning the relative relation of components in time.

5

Stream\_path\_end: This flag indicates the end of a stream path. A stream path is an ordered set of SubPlayItems. It defines the number and order of all SubPlayItems belonging to the stream path. The first stream path starts with the first SubPlayItem and ends with the first SubPlayItem having the Stream\_path\_end flag set "true". The second stream path starts with the first SubPlayItem following the previous stream path and ends with the first SubPlayItem having the Stream\_path\_end flag set "true", and so on. The last stream path ends with the last SubPlayItem. Setting the Stream\_path\_end flag "true" for the last SubPlayItem of the PlayList is optional. All SubPlayItems of a stream path shall have the same SubPlayItem\_type.

20 Playing back a stream path will decode the consecutive set of SubPlayItems belonging to the stream path including either the first SubPlayItem having the Stream\_path\_end flag set "true" or the last SubPlayItem of the PlayList.

25 The Transport Stream (TS) is organized according to the MPEG-2 Systems standard as specified in ISO/IEC 13818-1, Generic coding of moving pictures and associated audio information. However, in order to guarantee a conflict free playback during decoding and at the same time a late and independent addition of content, e.g. the adding of auxiliary subtitles after the main authoring has already been finalized, the following rules of restrictions for the transport streams are necessary:

35 The TS of PlayItems must contain a Program Association Table (PAT) and Program Map Table (PMT). They provide the PID table and language information for every TS component (elemen-

tary stream) within the multiplex.

The TS of SubPlayItems contains auxiliary streams. The preferred format of auxiliary streams again is a TS.

Within the TS of a SubPlayItem no PAT is allowed. This prevents conflicts with the TS of the PlayItem.

The TS of a SubPlayItem must contain a PMT whose PID is not used within the TS of PlayItems.

All PID associated to elementary streams within all TS for PlayItems as well as SubPlayItems must be different.

10

The advantage of the TS rules listed above is, that a single PID filter is sufficient for decoding all elementary streams. When violating the TS rules a PID re-stamping before buffering the input data or the separating of different buffers becomes necessary.

15

The invention has several advantages:

It provides more flexibility for the authoring of pre-recorded blue-ray discs. E.g. after the finalization of the main AV multiplex, additional languages can easily be added to the disc at a later time. This is because an auxiliary AV multiplexes containing e.g. audio and sub-title information in other languages can be prepared independently and added to the disc image without changing the basic AV multiplex (no recoding, re-multiplexing required).

20

There are no limitation for the maximum number of audio, subtitle, video angles, AV formats etc. caused by the bandwidth given for the multiplex. The limitation is simply defined by the volume capacity.

25

It allows optional binding of external sources to disc content e.g. a special sound track from hard disc or internet server, resulting in added value by binding new streams to pre-recorded discs.

30

Furthermore, rules are provided for simplified decoding of

elementary streams coming from different transport streams and for seamless stream switching (e.g. for multi-angle videos) across different transport streams.